

**Registry Modifications During Installation:**

When Dialpad Everywhere is installed, the following registry folders are created:

HKEY\_LOCAL\_MACHINE/SOFTWARE/Microsoft/Windows/CurrentVersion/Explorer/Helper Objects/{16122F02-9713-11D3-9744-005004116944}

HKEY\_CLASSES\_ROOT/IEHooker.CIEHooker.1  
 HKEY\_CLASSES\_ROOT/IEHooker.CIEHooker.1/CLSID  
 HKEY\_CLASSES\_ROOT/IEHooker.CIEHooker  
 HKEY\_CLASSES\_ROOT/IEHooker.CIEHooker/CLSID  
 HKEY\_CLASSES\_ROOT/IEHooker.CIEHooker/CurVer

The script for modifying the registry is contained in the CIEHooker.RGS file (text shown here):

```
HKCR
{
    IEHooker.CIEHooker.1 = s 'CIEHooker Class'
    {
        CLSID = s '{16122F02-9713-11D3-9744-005004116944}'
    }
    IEHooker.CIEHooker = s 'CIEHooker Class'
    {
        CLSID = s '{16122F02-9713-11D3-9744-005004116944}'
        CurVer = s 'IEHooker.CIEHooker.1'
    }
    NoRemove CLSID
    {
        ForceRemove {16122F02-9713-11D3-9744-005004116944} = s 'CIEHooker Class'
        {
            ProgID = s 'IEHooker.CIEHooker.1'
            VersionIndependentProgID = s 'IEHooker.CIEHooker'
            ForceRemove 'Programmable'
            InprocServer32 = s '%MODULE%'
            {
                val ThreadingModel = s 'Apartment'
            }
            'TypeLib' = s '{16122EF1-9713-11D3-9744-005004116944}'
        }
    }
}

HKLM
{
    SOFTWARE
    {
        Microsoft
        {
            Windows
            {
                CurrentVersion
                {
                    Explorer
                    {
                        'Browser Helper Objects'
                    }
                }
            }
        }
    }
}
```

005004116944}

{16122F02-9713-11D3-9744-

**Registry queries for setting/determining if phone parsing is turned on/off:**

```

void EnablePhoneParse(BOOL bEnablePhoneParse)
{
    HKEY hAppKey;
    DWORD dwDisposition;

    if(RegCreateKeyEx(HKEY_LOCAL_MACHINE,
TEXT("Software\\DialPad.com"), 0, NULL,
        REG_OPTION_NON_VOLATILE, KEY_WRITE, NULL, &hAppKey,
        &dwDisposition)
        == ERROR_SUCCESS)
    {
        RegSetValueEx(hAppKey, TEXT("EnablePhoneParse"), 0,
REG_BINARY, (LPBYTE)&bEnablePhoneParse, sizeof(WORD));
        RegCloseKey(hAppKey);
    }
}

BOOL IsEnablePhoneParse()
{
    HKEY hAppKey;
    DWORD bEnablePhoneParse = 0;
    DWORD ulSize;

    if(RegOpenKeyEx(HKEY_LOCAL_MACHINE,
TEXT("Software\\DialPad.com"), 0, KEY_READ,
        &hAppKey) == ERROR_SUCCESS)
    {
        ulSize = sizeof(DWORD);
        RegQueryValueEx(hAppKey, TEXT("EnablePhoneParse"), NULL,
NULL, (LPBYTE)&bEnablePhoneParse, &ulSize);
        RegCloseKey(hAppKey);
    }
    return (BOOL)bEnablePhoneParse;
}

```

005004116944"249999